

CLR-GW-GL Gateway LoRa/GSM/LAN

DISPOSITIVO GATEWAY, NODO CENTRALE DELLA RETE "COLoRa", NECESSARIO PER METTERE IN COMUNICAZIONE I NODI DELLA RETE "LoRa" CON IL WEB VIA GSM O LAN



OVERVIEW

- ALIMENTAZIONE 220VAC
- LONG RANGE – 868MHz
- CONNETTIVITA' GSM/LAN
- PLASTIC CASE CON DIN RAIL MOUNT
- FACILE DA INSTALLARE
- APPLICAZIONI INDOOR/OUTDOOR – IP67
- ANTENNA ESTERNA PER AUMENTARE CONNETTIVITA' LoRa

APPLICAZIONI

- WIRELESS NETWORKS/SENSORS
- SMART METERING
- HOME, BUILDING AND INDUSTRIAL AUTOMATION
- REMOTE CONTROL
- MONITORING

SPECIFICHE

<i>Parameter</i>				<i>Unit</i>
Power Supply	110-260			Vac
Frequency	50			Hz
Dimension(L x W x H)	140 x 125 x 90			mm
Operating Temperature	-40	-	+85	°C

INTERFACCIA GMS

- GSM/GPRS Quad-band module (850/900/1800/1900MHz);
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
 - Class 4 (2 W @850/ 900 MHz)
 - Class 1 (1 W @ 1800/1900MHz)
- Connettore SMA per antenna GSM;
- SIM Slot

INTERFACCIA ETHERNET

- IEEE 802.3 compatible Ethernet Controller;
- Integrated MAC and 10Base-T PHY;
- Support one 10/100Base-T Port

